

RECLAMATION

Managing Water in the West

**Protocol for Measuring
the Performance of
Reinforcing Steel
Corrosion Mitigation
Technologies for
Concrete Repairs**


**Kurt von Fay
Bureau of Reclamation
Materials Engineering and
Research Laboratory**



U.S. Department of the Interior
Bureau of Reclamation

Key scenario:

- An existing reinforced concrete structure has some corrosion damage evident or imminent. Spall repairs are obvious but what technology(ies) does one use to repair the spall and to minimize the frequency and quantity of subsequent repairs on the whole structure?
- Designers and owners are approached by dozens of product suppliers without much standardized testing or independent guidance.
- There is a strong feeling of paralysis or doubt on every product / technology.



RECLAMATION

13 Goals of Vision 2020

1. Mechanism for industry cooperation
2. Speed process of document creation
3. Create repair code
4. Performance based specifications
5. Improve repair material properties
6. Worker friendly materials and methods
7. Performance modeling system
8. Industry strategic research plan
9. Increase industry professionals
10. Better contract documents
11. Owner education tools
12. Condition assessment standards
13. Special repair systems

Vision 2020
A Vision for the Concrete Repair, Protection
and Strengthening Industry

2020
V I S I O N

Develop a means for predicting repair system performance to help ensure the use of proper materials, design details and installation methods based upon predictive models validated by experience..

RECLAMATION

Strategic Overview

Vision 2020 Objective:

- **Develop a test protocol which can be used to evaluate the effectiveness of reinforcement corrosion mitigation techniques for existing structures**
 - **Should be a flexible testing program that would properly evaluate the performance of current corrosion mitigation options while allowing for future innovations**

Goal and Objective

- **Program goal is to develop data needed to validate a protocol for evaluating products that mitigate corrosion in reinforced concrete.**
 - **Products evaluated under similar conditions**
 - **Aid to accelerate the development of new technologies**
- **Both topical surface treatments and patching repair technologies are used.**
- **Program is close to completion**
- **DOES NOT GRADE TECHNOLOGIES – Simply allows for generating test data using a relevant, consistent, repeatable process**

History of the Project

- **2003 - Vision 2020**
- **Industry Experts Suggest “Test Protocol to Measure Performance of Corrosion Prevention and Mitigation Technologies for Existing Concrete Structures”**
- **2008 Organizational meetings**
- **2009 Draft**
- **2010 ACI Foundation Funds through SDC**
- **BOR Administering Contract for Phase 1**

Expert Panels 2008

TAMPA FL July 2008

- Peter Emmons (Structural Group)
- Leandro Etcheverry (WP Moore)
- Yash Paul Virmani (FHWA)
- Alberto Sagues (U. of South Florida)
- Matt Miltenberger, Mukul Dehadbrai (Tourney Consulting)
- Daryl Little (US Bureau of Reclamation)
- Bill Hartt (Florida Atlantic U. - Hartt & Assoc.)
- Jack Bennett (J.E. Bennett Consultants)
- Paul Noyce (Electrotech)
- Jacques Marchand (U. of Laval)
- Kelly Page (ICRI/Repair Council)
- Tony Nanni (U. of Miami - ACI TAC)
- Fred Goodwin (BASF Construction Chemicals)

Chicago IL Sept. 2008

- P. Emmons (Structural Group)
- P. Tourney (Tourney Consulting)
- D. Little (Bureau of Reclamation)
- K. Page (ICRI)
- J. Marchand (SEM Laboratories & U of Laval)
- F. Goodwin (BASF Construction Chemicals)
- A. Sagues (U of South Florida)
- A. Nanni (U of Miami and ACI TAC)

Primary Authors



M. Miltenberger (Tourney Consulting)

J. Marchand (U. of Laval / SEM Labs.)

RECLAMATION

What is in the Protocol?

- **Pallet size specimen**
 - Small enough for handling and controlled conditions
 - Large enough to properly evaluate
- **Relevant results for an array of concrete materials and treatment options**
- **Repeatability and reproducibility evaluation prior to evaluation scale-up**
 - 100 repeatability slabs
- **Corrosion initiation in ~ 1 year**
- **Treatment effectiveness in ~ 6 months by monitoring**
 - 3 non-proprietary topical (surface applied) treatments
 - 3 non-proprietary repair (integral) options
- **Eventual autopsy ~ 24 months**




Evaluation of Test Protocol

- Concrete cover, 0.75 and 1.50 inches
- Water-to-cement ratios, 0.40, 0.50, 0.60
- Effectiveness of various end bar protection techniques
- Methods to accelerate corrosion
- Test corrosion mitigation mechanisms
 - Various mechanisms
 - Ability to reduce corrosion rates


Evaluation Material Types

- **Integral**
 - Applied within the repair material
 - Reinforcing steel coatings
 - High-performance repair materials
 - Repair materials with containing corrosion inhibitors
 - Polymer concrete
 - Discrete galvanic cathodic protection anodes
- **Surface Applied**
 - Applied to surface of concrete
 - Penetrating sealers
 - Coatings
 - Chemical corrosion-inhibitors
 - Combined mechanism products



Materials (continued)

- **Cement**
 - ASTM C150 I/II 564 lb/yd³
- **Aggregate**
 - Fine Aggregate ASTM C33
 - Coarse Aggregate ASTM C33 Gradation No. 67 Limestone
- **Admixtures**
 - Air entrained 6%+/-1
 - Type A water reducer
- **Slump 5-8 inches**





RECLAMATION

Materials (continued)


- **Report**

- Density ASTM C138
- Slump ASTM C143
- Air Content ASTM C231
- Temperature ASTM C192



- **Cast**

- C39 Compressive Strength 21 4x8"
- ASTM C1202 RCP 12 4x8"
- ASTM C1556 Cl- Diffusion 6 4x8"
- ASTM C642 Density, Absorption Voids 2 4x8"
- BS1881 Water Absorption 4 3x6"



RECLAMATION



U.S. Department of the Interior



World-class engineering, science, research, and support services for projects related to water resources


RECLAMATION

BUREAU OF RECLAMATION

1902

- 17 Western States
- 600 Dams and Reservoirs *~RECREATION~*
- Largest Wholesaler of Water
 - 31M people
 - Irrigation to 10M acres of farmland
 - 60% of nations vegetables & 25% of fruits and nuts
- Second Largest producer of Hydroelectric Power
 - 58 Power Plants
 - 40 Billion kw hours of electricity
 - Nearly \$1 Billion in revenue
 - To 6M homes

RECLAMATION



**Hoover
Dam**



**Grand
Coulee Dam**




Civil Engineering
Geotechnical



Environmental
Resources



Water Resources



654

330 engineers,
134 scientists,
135 technical support,
55 administrative support

Infrastructure
Services

Laboratory



RECLAMATION

Contract No. R10PC80497

- 2010 ACI Foundation Funds through SDC
- Funds acceptable through authority of the Contributed Funds Act
- BOR to Administer Project Phase 1
- First step – Turn proposed protocol into a statement of work for a competitive bidding process
- Determined suitable for a small business set-aside
- Awarded to Tourney Consulting Group, LLC Kalamazoo, MI using a competitive bidding process in September 2010.

Contract Committee


- **SDC charged with forming a committee to determine**
 - **Specific technologies and number of technologies to use**
 - **When to apply/use corrosion mitigation technologies**
 - **Answer other questions as they come up**
 - **Review documents produced as a result of this work**

Specimen Types

- **Slabs**
 - Monolithic slabs for Surface Applied techniques
 - Hot spot slabs for Integral techniques
- **Materials**
 - Three W/C ratios
 - 0.4, 0.5, and 0.6
 - Two Reinforcement cover depths
 - 0.75 in. and 1.5 in.
 - Three Reinforcing bar end treatments
 - Cement paste with calcium nitrite
 - 10% H₂SO₄ pickle (ASTM G 109)
 - 0.1N Hot NaOH




Batch Castings




Batch No.	W/C	Quantity of Specimens		Type (Comment)
		0.75" Cover	1.5" Cover	
1	0.4	5	15	Repair (15 hotspot + 5 plain)
2	0.6	5	15	Repair (15 hotspot + 5 plain)
3	0.5	10	10	Topical
4	0.5	10	10	Topical
5	0.5	10	10	Topical







100 total slabs

20 slabs per 4 yard batch of concrete

- Group of 20 slabs with W/C 0.4 
- Group of 20 slabs with W/C 0.6 
- Group of 60 slabs with W/C 0.5 

60 Surface Applied slabs 
 30 with 1.5 in cover 
 30 with 0.75 in cover 

40 Integral Repair Slabs 
 10 with 0.75 in cover 
 30 with 1.5 in cover 


3 End Treatments: Drill, tap, and install 1/4x20SS machine screw in end of bar, remove surface rust.



Clean 4" to SSPC SP15. Coat with .5 W/C cement paste with 1/4 of mix water consisting of 30% CaNO₃ solution. Cover paste with heat shrink tubing. After casting and wiring, cover end with epoxy.




Per G109 -cover 4"-8" with electroplaters tape, pickle end 4" in 10% H₂SO₄ 10-15 min., rinse, wire brush to SSPC SP15, cover end 5" with neoprene tubing, fill with epoxy. After casting and wiring, cover end with epoxy.



Cover 4"-8" with electroplaters tape, clean end 4" soak in 120F 0.1N NaOH 8 hr., rinse, cover end 5" with neoprene tubing, fill with epoxy. After casting and wiring, cover end with epoxy.


Monolithic Slab – Topical Treatment

0.5 w/c




30 slabs with $\frac{3}{4}$ -inch cover

30 slabs with 1.5-inch cover




30x36" W4/W4 6x6" WWF with 1" bottom Cover
 #4 Steel Reinforcing Test Bar

For RH, Resistivity, Cores
 4 SS Resistivity Pins
 NEMA 4 Connection Box



Top view of plain concrete specimens



Batch 1 – “Repair”


Batch 2 – “Repair”

Group of 20 slabs with W/C 0.4 

Group of 20 slabs with W/C 0.6 


5 Plain Slabs of Both W/C and $\frac{3}{4}$ ” Cover 


Cast Monolithically With Discontinuous Reinforcing Steel to Compare W/C effect on Cl⁻ Ingress





100 total slabs



20 slabs per 4 yard batch of concrete

• Group of 20 slabs with W/C 0.4 

• Group of 20 slabs with W/C 0.6 

40 Integral Repair Slabs

10 with 0.75 in cover  

30 with 1.5 in cover  

Construct Remaining 30 Slabs (15 from batch 1 and 2) with 1 ½" Cover and 9"W x 20"L x 3"D Blockout Form Extending Below FRP Bars.

Place Concrete Around Blockout

Place 3 Different Types of Concrete Inside Blockout Area for Both W/C.



5 Plain Concrete Depressed Cover 8" W X 15" L X 1" Deep Depression

5 High W/C Ratio Concrete >0.75



2 ft³ of W/C 0.4 mixed with 14.6 lbs Water &





2 ft³ of W/C 0.6 mixed with 6.3 lbs Water



5 Chloride Spiked Concrete (2 ft³ of Each W/C Mixed With 3 lbs CaCl₂)



Repair Area Slab 15 Hotspot, 5 plain




9"x20"x3"D Removable Blockout

30x36" W4/W4 6x6" WWF with 1" bottom Cover
27" FRP Cross Bar

#4 Steel Reinforcing Continuous Bar
6 20" #4 Steel Reinforcing Discontinuous Bar
Nylon Zip Ties Join FRP and Test Bars



For RH, Resistivity, Cores
4 SS Resistivity Pins
NEMA 4 Connection Box












RECLAMATION



Repair
Hotspot



Depressed Cover



Mixture Characterization



- Fresh Properties
- Compressive Strength (ASTM C39)
- RCP (ASTM C1202)
- Chloride Content (ASTM C1152)
- Bulk Diffusion (ASTM C1556)
- Density, Absorption, and Voids (ASTM C 642)
- Water Absorption (BS 1881)
- STADIUM® Transport Properties



RECLAMATION

Next Steps

- Bull Float, Tool Edges, Float, & Light Broom Finish
- Cure Slabs With Blanket or Burlap & Plastic for 7 Days
- Dry Slabs One Week
- Connect Individual Reinforcing Bars to WWG With $1.0 \pm 0.1\Omega$ 1 Watt Shunt Resistor With >AWG 16 Stranded Copper
- Connections and Test Points Inside NEMA 4 Box
- Coat Sides of Slabs, Ends & Connections With Epoxy
- Adhere 2" Dam to Slab Perimeter with Neutral Cure Silicone
- Pond with $5.0 \pm 0.1\%$ NaCl Each 2 Weeks
- Dry Other 2 Weeks <70% RH
- Repeat Until Corrosion Onset



RECLAMATION





G4

G3

G2

6

7


V79

V70



Test Procedure

Ponding Cycle:
2 Weeks 5% NaCl Solution
2 Weeks Dry – Indoor




Outcomes

- **Time to Corrosion and Variation**
 - 180 bars $\frac{3}{4}$ " cover W/C 0.5
 - 180 bars 1 $\frac{1}{2}$ " cover W/C 0.5
 - 30 bars $\frac{3}{4}$ " cover W/C .4
 - 30 bars $\frac{3}{4}$ " cover W/C .6
- **Cl⁻ Threshold when corrosion is initiated**
- **Current when corrosion activity is sustained vs time to corrosion**
- **Repeatability of time to corrosion**
- **Batch to batch variation for each mix and cover**
- **Conditioning period prior to treatment vs depth of cover**
- **Water content vs time to corrosion**
- **Variability of macrocell corrosion measurements**
- **Determine minimum lot size for treatment evaluation**
- **Macrocell corrosion current vs**
 - Temperature
 - Internal RH
 - Cl⁻ contamination level for corrosion
 - Electrical resistance vs other variables
- **Effectiveness of different Hot Spot techniques for evaluation of internal treatments**
- **Effectiveness of different reinforcing bar end treatments**
- **Ability of program to evaluate different GENERIC corrosion mitigation treatments**


Corrosion Monitoring

Macrocell Corrosion


Current




Mat-to-Mat Resistance



Electrical Resistivity



Half-Cell Potential



Summary after about 6 months (4/11)

Corrosion Condition Summary (Surface Repair Slabs)

Surface Treatment Slabs 0.75" Cover					
Batch No.	Specimen ID	No. of Slabs	Cycle	Corrosion Initiation	Bars Corroding
1	0.40 w/c	5	6	100%	95%
2	0.60 w/c	5	6	90%	88%
3	0.50 w/c	10	5	82%	78%
4	0.50 w/c	10	5	88%	80%
5	0.50 w/c	10	4	85%	80%

Surface Treatment Slabs 1.5" Cover					
Batch No.	Specimen ID	No. of Slabs	Cycle	Corrosion Initiation	Bars Corroding
3	0.50 w/c	10	5	0%	0%
4	0.50 w/c	10	5	0%	0%
5	0.50 w/c	10	4	0%	0%

Product Selection

Patch Repair Treatments:

- Rebar Coatings
- Galvanic Anodes
- Mortars with Inhibitors

Electrochemical Treatments:

- Cathodic Protection
- Chloride Extraction
- Electro-Phoresis

Surface Treatments:

- Silane Sealers
- Epoxy/Resin Coatings
- Corrosion Inhibitors (Several Chemistries)
- Elastomeric Membranes
- Silicates

Surface Treatment Program

Surface Treatment:

- Allow slab to dry for a minimum of 1 week
- Do not repair hotspot (or eliminate?)
- Clean and prepare surface using abrasive technique (shotblasting)
- Install 3 grout-filled potential wells with caps for membrane & coating series
- Photo document preparation
- Apply surface treatment/coating according to manufacturer instructions
- Allow treated surface to remain dry for at least one week prior to ponding
- Reinstall dams
- Resume cyclic ponding and monitoring

Monitoring:

- Macrocell current between top and bottom mat across 1-ohm shunt
- Microcell corrosion current in and adjacent to hotspot (quarterly)
- Corrosion potential map of surface
 - ~12-inch grid or potential wells @ end of wet cycle)
- Internal temperature and RH
- Internal electrical resistivity (4-pin measurement)

Batch Castings

		Quantity of Specimens		
Batch No.	W/C	0.75" Cover	1.5" Cover	Type (Comment)
1	0.4	5	15	Repair (15 hotspot + 5 plain)
2	0.6	5	15	Repair (15 hotspot + 5 plain)
3	0.5	10	10	Topical
4	0.5	10	10	Topical
5	0.5	10	10	Topical

Topical Mitigation Treatment Timing

Corrosion Mitigation should be applied when:


- 750 Coulombs is reached on average; and
- At least half the rebar have reached ≥ 750 C; or
- Any single rebar has exceeded 5000 C
- Before Cracking

Treatments Applied – 0.75” Cover Topical Slabs – Applied June 2011

Topical Treatments

- A – Inhibitor – Calcium Nitrite
- B – Sealer – 40% silane
- C – Membrane Urethane/Epoxy Coating

Treatment “A”



Treatment “B”




Treatment “C”



Potential Well Construction

Potential wells were installed to enable half-cell potential measurements beneath the membrane



Each potential well functions for measuring two rebar

Treatments Applied - .75 inch cover

- Testing Recently Completed

of Slabs per Treatment

Batch #	Control	Topical Treatment			TOTAL
		A	B	C	
1 (0.40 w/c)	3	2	-	-	5
2 (0.60 w/c)	3	2	-	-	5
3 (0.50 w/c)	4	2	2	2	10
4 (0.50 w/c)	4	2	2	2	10
5 (0.50 w/c)	4	2	2	2	10

Batch #'s 1, 3, & 5 treated on June 7, 2011

Batch #'s 2 & 4 treated on June 21, 2011

Destructive Analysis Of .75 Inch Cover Slabs

- **For slabs in batches 3 – 5**
- **One of each slab type – Control and treatment**
- **Results in December**

Destructive Analysis

- **Two slabs autopsied**
 - Slab 46 with low macrocell corrosion rate
 - Slab 53 with high macrocell corrosion rate
- **Tests performed**
 - Macrocell
 - Corrosion potential map
 - Chloride profile at most negative and positive corrosion potential site
 - Degree of corrosion
 - Exam of end treatments
- **Findings**
 - Good correlation between corrosion damage macrocell current
 - Potential mapping identifies high damage to reinforcing bars
 - Average total macrocell corrosion for applying repairs is valid


Destructive Analysis – Slab #53

- Batch #3
- 0.50 w/c
- 0.75" Cover
- Treated w/ CNI






Half-Cell Potential, -mV CSE₇₇



Slab #53								
Rebar	7	6	5	4	3	2	Average	Total
Integrated Current (Coulombs)	10128	34483	656	0	10669	35106	15174	91042
Half-Cell Potential (mV CSE ₇₇)	-514	-562	-428	-395	-529	-508	-489	-

Destructive Analysis – Slab #46

Batch #3
0.50 w/c
1.5" cover
No treatment
- Autopsy
prior to
treatment to
quantify level
of corrosion
at time of
treatment





Topical Treatment – 1.5 inch Cover

Batch Castings

Batch No.	W/C	Quantity of Specimens		Type (Comment)
		0.75" Cover	1.5" Cover	
1	0.4	5	15	Repair (15 hotspot + 5 plain)
2	0.6	5	15	Repair (15 hotspot + 5 plain)
3	0.5	10	10	Topical
4	0.5	10	10	Topical
5	0.5	10	10	Topical

Topical Slab Treatment Criteria

Corrosion mitigation should be applied when:

Level 1)

- 750 Coulombs is reached on average; and
- At least half the rebar have reached ≥ 750 C; or
- Any single rebar has exceeded 5000 C

Level 2) (Batch #5 Only)

- 1500 Coulombs is reached on average

Treatments started in May 2012

RECLAMATION

Topical Slab Treatment – 1.5-inch cover

Topical Treatments (Suggested based on Autopsy results)

- A - Calcium Nitrite Inhibitor (Do not retest)
- B - 40% Silane Sealer (*Test at 2 levels of corrosion activity)
- C - Urethane/Epoxy Coating Membrane

of Slabs per Treatment (Better Statistics)

Batch #	Control	Topical Treatment			TOTAL
		A	B	C	
1 (0.40 w/c)	-	-	-	-	-
2 (0.60 w/c)	-	-	-	-	-
3 (0.50 w/c)	3	-	3	3	10
4 (0.50 w/c)	4	-	3	3	10
5 (0.50 w/c)	4	-	6*	-	10

First slab in Batch #3 autopsied to quantify corrosion

Patch Repair Program

Patch Repair:

- Concrete removal and patch repair using abrasive blast prep.
- Photo document patch preparation
- Reinstall dams as necessary
- Resume cyclic ponding and monitoring

Monitoring:

- Macrocell current between top and bottom mat across 1-ohm shunt
- Corrosion potential map of surface (~12-inch grid)
- Galvanic current (anode series only)
- Microcell corrosion rate (NDT) in and adjacent to hotspot (quarterly)

Hot Spot Treatments

Batch Castings

Batch No.	W/C	Quantity of Specimens		Type (Comment)
		0.75" Cover	1.5" Cover	
1	0.4	5	15	Repair (15 hotspot + 5 plain)
2	0.6	5	15	Repair (15 hotspot + 5 plain)
3	0.5	10	10	Topical
4	0.5	10	10	Topical
5	0.5	10	10	Topical

Hot Spot Repair Criteria

Corrosion mitigation should be applied when:

- 500 Coulombs is reached on average outside the hot-spot

Six slabs to be used for autopsies – 2 each at 500 C, 1000 C and 2000 C average or when testing is complete.

Hot Spot Treatments

Repair Treatments

- D – Repair Mixture, 0.40 w/c, 6.5 SK, Type I/II Cem (No SCMs), pea gravel
- E - Rebar coating (Same repair mixture)
- F - Galvanic anode (Same repair mixture)
- G – 40% Silane (Same repair mixture)

Quantity of Patch Repair Treatment Slabs							
Batch No.	Specimen ID	No. of Slabs	D	E	F	G	Autopsy
1	0.40 w/c (Chloride)	5	3	3	3	3	3
	0.40 w/c (High w/c)	5					
	0.40 w/c (Low Cover)	5					
2	0.60 w/c (Chloride)	5	3	3	3	3	3
	0.60 w/c (High w/c)	5					
	0.60 w/c (Low Cover)	5					


Repair Treatments

- D – Repair Mixture
- E - Rebar coating (Same repair mixture)
- F - Galvanic anode (Same repair mixture)
- G – 40% Silane (Same repair mixture)





RECLAMATION



Project Timeline

Current Status



Batch No.	w/c	Cover	Type	3/20/2012	4/3/2012	4/17/2012	5/1/2012	5/15/2012	5/29/2012	6/12/2012	6/26/2012	7/10/2012	7/24/2012	8/7/2012	8/21/2012	9/4/2012	9/18/2012	10/2/2012	10/16/2012	10/30/2012	11/13/2012	11/27/2012	12/11/2012	
Cycle				19	20	21	22	23	24	25	26													
1	0.4	1.5"	Repair																					
		0.75"	Topical																					
Cycle				8	19	20	21	22	23	24	25	26												
2	0.6	1.5"	Repair																					
		0.75"	Topical																					
Cycle				18	19	20	21	22	23	24	25	26												
3	0.5	1.5"	Topical																					
		0.75"																						
Cycle				7	18	19	20	21	22	23	24	25	26											
4	0.5	1.5"	Topical																					
		0.75"																						
Cycle				17	18	19	20	21	22	23	24	25	26											
5	0.5	1.5"	Topical																					
		0.75"																						


- Repair Treatments Applied
 - 1.5" Cover Slabs (Batch 1-2, as criteria is met)
 - 50% of repair slabs have been treated or destructively analyzed
- USBR has started the write up of the final released protocol for distribution and use in commercial assessments and specifications. Expected release in early 2013.

Notes for Future Discussions

- **Make depressed cover for hotspots $\frac{1}{4}$ inch less than nominal cover – $\frac{3}{8}$ inch cover worked well.**
- **Rebar End conditioning – cement paste and shrink wrap seem best**
- **1-inch cover with $\frac{1}{2}$ inch MSA seems like the best choice for topical and hot spot repairs**
- **Include corrosion potential mapping**
- **Move ponding dams in from the edge to prevent damage to ends of rebar**
- **Do treatments at different corrosion levels**

Concrete Cover

- 0.75" Cover – Corrosion initiation too quickly
- 1.5" Cover – Too long for accelerated test?



Thank you!!

Questions?

RECLAMATION