



Kevin K Goudarzi, PE

Project Manager

KGS Construction Services Inc

Email: Kgoudarzi@kgsconstruction.com

Cell: 703-853-0092



Seismic Retrofitting of a 28 story hotel

Kevin Goudarzi, PE



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Content

1

Introduction

2

Earthquake hazard zone

3

Existing Condition

4

Structural analysis

5

Carbon Fiber, CFRP

6

Material Testing

7

Dampers

8

Summary

9

References




1. Introduction



Bam earthquake

The 2003 **Bam earthquake** struck the Kerman province of southeastern Iran at 5:26 AM on December 26. The shock had a moment magnitude of 6.6 . The earthquake was particularly destructive in Bam, with the death toll amounting to at least 26,271 people and injuring up to 30,000. The effects of the earthquake were exacerbated by the use of mud brick as the standard construction medium; many of the area's structures did not comply with earthquake regulations set in 1989.



Earthquake damage to the city

6



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Bam Citadel before earthquake

- It was built 2500 years ago and
- It is the largest Adobe in the world
- It was almost completely destroyed by the earthquake On December 26, 2003.



7



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

Bam Citadel after earthquake

8



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco



1.A- Seismic Retrofitting of a 28 Story Hotel

- The 28 story Azadi Hotel was built during the 1970's by a German engineering company.
- The building is made of concrete and has continuous walls from the 2nd floor to the 28th floor.
- These walls partition the rooms and are made of reinforced concrete and they work as the preliminary resisting elements for the seismic.
- The major deficiency was the existence of a soft story in the lobby, including poor quality concrete columns of up to 36 feet high.

9



The building before improvement

10



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

The building after renovation

11



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE


2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

2.

Earthquake hazard zone



The Fault map in project Location



13



Fault line near
to project
location



14



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

3.

Existing Condition



The existing column with poor concrete and no lateral reinforcement at the bottom of the column

16



Huge beams over columns at lobby

17



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco


4.

Structural analysis



3D Modeling of the structure

19



Structural Analysis


- The building is made of concrete and has continuous walls from the 2nd floor to the 28th floor.
- These walls partition the rooms and are made of reinforced concrete and they work as the preliminary resisting elements for the seismic. This is advantageous during an earthquake.
- The columns in the lobby, which were introduced to create a commercial space in the first story, are highly critical. These columns have very little stirrups and consist of poor quality concrete with average concrete compressive strength of 2900 psi.
- the walls stop at ground level, introducing a discontinuity to the lateral load resisting system. This results in a structure with a soft story floor.

Studies, Design and Supervision

- SMTeam GmbH Co. from Switzerland was the authorized company for design and supervision of seismic rehabilitation project.
- Radyab Co was the local engineering consultant in charge for local design and supervision.
- EMPA Institute from Switzerland as the consultant was responsible for quality control of the materials and equipment.

Displacement of structure under lateral loads

22



Local Seismic code

- Soft Story: The story in which, lateral stiffness is less than 70 percent of that of the story above or less than 80 percent of the average stiffness of the three above stories.
- Building Classification according to Importance:

- ❖ Group1- Buildings with “Very High Importance”

This group includes buildings that their post-continuous earthquake operation is of special importance and any discontinuity in this regard leads to an indirect increase in casualties and damages. Hospitals, clinics, fire stations, police stations, etc.

Building Classification according to Importance:

❖ Group2- Buildings with “High Importance”

a- Buildings whose damage results in great loss of life such as: schools, mosques, stadiums, cinemas and movie theatres, etc.

b- Buildings whose damage results in loss of national heritage. These include: museums, libraries and other places where national documents and valuable items are preserved.

c- Industrial buildings and facilities whose failure, may result in environmental pollution or widespread fire, such as refineries, fuel storage tanks and gas supply centers.

Building Classification according to Importance:

- ❖ Group3- Buildings with “Moderate Importance”

All buildings that are within the scope of this Code, except those included in other categories, fall in this group. These include: residential, office and commercial buildings, hotels, etc.

- ❖ Group4- “Buildings with Low Importance”

a- Buildings with low risk of damage and loss of life due to their failure such as agricultural warehouses and poultry farms.

b- Temporary buildings with an operational life of less than two years.

Earthquake base shear load

Base Shear, V

The minimum base shear or the sum of the horizontal seismic loads, in each direction of the structure, shall be determined from:

$$V=CW$$

Where:

V= The shear force at base level.

W= The total seismic weight of building, that is equal to the total dead load plus, a percentage of live and snow loads

C= The seismic coefficient, that is determined from the following

C Factor in base shear force

$$C = ABI/R$$

- A= Design base acceleration ratio (ratio of seismic acceleration to gravity acceleration, g)
- B= Building response factor determined from the design response spectrum,
- I= Importance factor
- R= Building behavior factor,

Percentage of live and snow loads in the seismic weight of the building

Location	Percentage of live load
Sloped roofs with a slope equal to or greater than 20%(1)	----
Flat roofs or roofs with a slope less than 20%	20
Residential buildings, Offices, hotels and garages	20
Hospitals, schools, shopping centers and public buildings	40
Storages and Libraries	60
Water tanks and other liquid storage tanks and silos	100


Design base acceleration ratio for various seismic zones

Zone	Description	Design base acceleration
1	Very high level of relative seismic hazard	0.35
2	High level of relative seismic hazard	0.30
3	Intermediate level of relative seismic hazard	0.25
4	Low level of relative seismic hazard	0.20

Building Importance Factor(I)

Building Classification	Importance Factor
Group 1	1.4
Group 2	1.2
Group 3	1.0
Group 4	0.8

The seismicity and seismotectonic study



The seismicity and seismotectonic studies on site

32



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

The seismicity and seismotectonic studies on site

33




The seismicity and seismotectonic studies on site

34



Columns layout

35



"-1BASEMENT" COLUMN ARRANGEMENT PLAN
SC 1: 25




5. Carbon Fiber (CFRP)



Columns Confinement with CFRP

Column Confinement with CFRP:

- Enhancing load carrying capacity
- Increasing deformation capacity usually in the case of seismic upgrading
- Increasing shear capacity



Surface preparation for CFRP installation

38



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

**Excavating down
to the foundation
to install CFRP**



39



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Carbon Fiber wrapping on the columns

40



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Carbon Fiber installation on the shear walls

41



**Rectangular
columns confined
by CFRP, the
bottom and top
sections of the
column has been
reprofiled to curvy
shape**



42



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

**Attached
buildings columns
wrapped by CFRP**



43



**INTERNATIONAL
CONCRETE REPAIR
INSTITUTE**

6.

Material Testing



**Pull-off test on
surface
preparation
material**

45



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Pull-off test on CFRP

46



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

**Pull-off test on
CFRP showing
successful
bonding, Failure
in concrete**

47



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

**Columns built in
lab to simulate
the hotel's
columns under
earthquake load**

48



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

**Scaled columns in
lab tested with
and without CFRP**



49

sample
preparation for
CFRP and epoxy
testing



50



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

sample
preparation for
CFRP and epoxy
testing



51



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE


2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

sample
preparation for
CFRP and epoxy
testing

52



**CFRP sample after
failed under
tensile stress test**



53

Epoxy Testing

- Epoxy Test Result in Laboratory:
 - 1) Tensile strength: **42.1** N/mm² ± 7.4%
 - 2) Tensile elastic modulus: **4'485** kN/mm² ± 1.5%
- Specified values in the Product Data Sheet:
 - 1) Tensile strength: **30** N/mm² (7 days at 23°C)
 - 2) Tensile elastic modulus: **4'500** N/mm² (7 days at 23°C)

Carbon Fiber Testing

- CFRP Composite Test Result in Laboratory:
 - 1) Ultimate load **387** kN \pm 7.6% per 1 m' laminate width
 - 2) Tensile elastic modulus **30.4** kN/mm² \pm 2.8% based on a thickness of 0.9 mm
- Specified values in the CFRP Product Data Sheet:
 - 1) Ultimate load **360** kN per 1 m' laminate width
 - 2) Tensile elastic modulus **25.0** kN/mm² based on a thickness of 0.9 mm

Material Testing Assessment

- The measured strength (tensile and compression) and the elastic modulus of the using epoxy corresponds well or are even higher than the specified ones.
- The measured strength and elastic modulus of the CFRP composite impregnated with Epoxy corresponds well or are even higher than the specified ones.

7. Dampers





Recommended Damper Specifications

The following specifications were recommended:

- Maximum damper at maximum damper velocity of 1500 kN +/- 15% tolerance.
 - Maximum damper stroke: +/- 15 mm for the mitigation of earthquake vibrations
 - +/- 5 mm for the compensation of thermal expansion/contraction
 - +/- 3 mm for the installing tolerances
- ==> the maximum recommended stroke is +/- 23 mm

Damper locations plan



**Inverted V
bracing with
dampers**

60



**Inverted V
bracing with
dampers**

61



Dampers ready
for testing




62



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

Hydraulic Dampers in testing setup



63



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

8. Summary



Summary

- The preliminary design was to apply FRP to the columns and shear walls at the lobby level and the basement.
- It was clearly demonstrated that applying FRP alone could not be satisfactory.
- The FRP could solve the shear problem of the columns; however, the bending problems of the columns could not satisfactorily be solved.
- The columns drift too much, resulting into high bending moments.
- It was decided to introduce additional bracings with hydraulic dampers in the lobby level and in the first floor.
- In order to prevent overturning of the structure, and reduce moments and shears at the base, 16 hydraulic dampers were utilized in the lobby and first floor.
- More than 215,000 square feet of carbon fiber reinforced polymer was also used to reinforce the columns and the shear walls in the lobby and the two basements floors. The dampers also, were installed with help of inverted V-bracings.

Summary

- Checking the shear forces, moments and axial loads with the allowable shear forces and moment-axial load capacity diagrams shows that the building can undergo the 475year earthquake without major damage.
- The retrofitted solution has following advantages:
 1. Reducing of the drift of the lobby that resolved the soft story issue
 2. Reduction of the shear and bending stresses
 3. The loads in the bracing shall be in order of acceptable levels
 4. The dampers allow a seismic health monitoring of the hotel in future

The hotel before
improvement

67



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | seismic solutions | April 11-13 | San Francisco

The hotel after
improvement

68



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

Project Complete

69



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE

2018 Spring Convention | **seismic**solutions | April 11-13 | San Francisco

References



References

- 1) Sassan Mohasseb and Bahareh Abdollahi. *“Soill-Structure Interaction Analyses Using Cone Models”*, 2009.
- 2) Sassan Mohasseb and Samaneh Daviran. *“Seismic Retrofitting of a 28 Story Building Including Soil-Structure Interaction Effects”*, 2014.
- 3) *Radyab, Azadi hotel project documents, reports and test reports from EMPA and SMTEAM*
- 4) *Dr. Zare, “the seismic hazard analysis studies of Azadi Hotel”, 2005*
- 5) *Iranian Code of Practice for Seismic Resistant Design of Buildings, Standard No.2800*
- 6) *A.A Moinfar, A. Naderzadeh, M.H Nabavi, “New Iranian Seismic hazard zoning map for new edition of seismic code and its comparison with neighbor countries”*
- 7) *Mehran Arian, Nooshin Bagha, “Active Tectonics of Tehran Area, Iran”*
- 8) *Masoud Motavalli, “Externally Bonded FRP: Confinement Fibre Composites, FS17”,*

Thank You!

Do you have any questions?

Kevin K Goudarzi, PE

Project Manager

KGS Construction Services Inc

Email: Kgoudarzi@kgsconstruction.com

Cell: 703-853-0092



72



INTERNATIONAL
CONCRETE REPAIR
INSTITUTE